

The Oil&Steel Octopus 14 spider platform provides a maximum working height of 14m and maximum outreach of 6.5m (one operative operation).

At just 780mm wide in tracking mode it can be moved through a single doorway or narrow gate, making it ideal for operation in very confined space.

Power options

- Low emission petrol or diesel engine
- Bi-energy – petrol or diesel engine with a 110v mains electric motor
- All-electric battery power



14m max working height



IPAF - Static Boom (1b, 1b+)



Technical Specifications

Max Working Height:	14m
Platform Height:	12m
Max Working Outreach:	6.5m
Load Capacity:	200kg (2 person restricted)
Stowed Height:	1980mm
Stowed Length:	4100mm
Stowed Width:	1400mm (with basket)
Basket Dimensions:	L1400 x W700 x H1100mm
Removable Basket	Standard via quick release
Outrigger Footprint:	2700mm x 2700mm
Tracks:	Fixed as standard
Power Source :	12hp Petrol
Wireless Remote Control:	Optional
Total Machine Weight:	1760kgs

Optional Accessories

- Wireless radio remote (outriggers & drive functions)
- Tracks – optional extending
- Non marking tracks
- Automatic stabilisation
- 9hp diesel engine (+10kgs)
- All electric battery power (+60gs)
- Octopus 14 with double working area fixed track (1760kgs)
- Octopus 14 with double working area widening track (1810kgs)
- Octopus 14 with single working area + fixed track (1910kgs)
- Octopus 14 with single working area + widening track (1960kgs)
- Water / air line supply to basket (fitted as standard)

Available with the Wireless Remote Control





Octopussy has an ultra-compact chassis enabling it to access sites through narrow gates

Working envelope



Dimensions

